



# S16419

26T8/LED/HO-SIGN/64-865/BP  
 26W T8 LED; 6500K; 3650 Lumens; 120-277V; Double Side  
 LED; Type B; Ballast Bypass; Single Ended Wiring

## Features

- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage\*
- NSF Approved
- No ballast or external driver required



S16419

Item Number	UPC	Voltage	Watts	Operating Frequency	Power Factor	Lamp Shape	Base
S16419	045923164194	120-277	26	50/60Hz	0.90	T8	Recessed Double Contact HO/VHO

  

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	Nominal Length	MOD In Inches	Initial Lumens
R17d	26T8/LED/HO-SIGN/64-865/BP	Non-Dimmable	Frosted	61-7/8"	64"	1.00"	3650

  

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	6500	Daylight	83	330	-30C (-22F) to a maximum of +45C (+113F)	10	Sleeve

  

CEC Status	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Lawful for sale in California	Yes	Yes	cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

