



S23150

63W/LED/CCT/100-277V/EX39

GENERAL SPECIFICATIONS

Wattage:	63W/54W/45W
Lumen Output:	8820L/7560L/6300LL
Color Temperature:	3000K/4000K/5000K
Base:	Mogul Extended



TECHNICAL SPECIFICATIONS

Wattage:	63W/54W/45W
Volts:	100V-277V
HID Equivalent:	250W/200W/175W
Filament:	LED
Base:	Mogul Extended
ANSI Base:	EX39
Finish:	White
Housing Color:	Dark Gray
Hours Rated:	50000H
Color Temperature:	3000K/4000K/5000K

CRI:	80CRI
Lumen Output:	8820L/7560L/6300L
Dimmable:	Yes-Dimmable
Dimming Function:	Dimmable only via the wattage/lumen selectable dial included on lamp
Burning Position:	Base Up, Base Down, or Horizontal
Beam Spread:	300D
Power Factor:	>0.9
Operating Temp:	-40C (-40F) to a maximum of +60C (+140F)
Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Technology:	LED

DIMENSIONS

MOL:	10.28"
MOD:	3.35"
Weight:	1.80
Min. Compartment Size:	Length: 7.88 in. Width: 7.88 in.

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-ZHMICR
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL File Listing:	US/CN - E356817; US/CN - E335148
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923231506	Inner UPC:	20045923231500	Case UPC:	10045923231503
Each Quantity:	1	Inner Quantity:	6	Case Quantity:	12
Each Dimensions:	11.57 x 3.66 x 3.66"	Inner Dimensions:	11.54 x 7.95 x 12.17"	Case Dimensions:	16.73 x 12.28 x 13.15"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
May 22, 2022