SATCO" NUVO"



S28930

40W/LED/WP/CCT/EX39/100-277V

GENERAL SPECIFICATIONS

Shape: Corncob Wattage: 20W/30W/40W Lumen Output: 3200L/4700L/6000LL Color Temperature: 3000K/4000K/5000K Mogul Extended Base:













TECHNICAL SPECIFICATIONS

Wattage:	20W/30W/40W
Volts:	100V-277V
HID Equivalent:	175W
Shape:	Corncob
Filament:	LED
Base:	Mogul Extended
ANSI Base:	EX39
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3000K/4000K/5000K

CRI:	80CRI
Lumen Output:	3200L/4700L/6000L
Dimmable:	Yes-Dimmable
Dimming Function:	Dimmable only via the wattage/lumen selectable dial included on lamp
Burning Position:	Horizontal Operation
Beam Spread:	180D
Power Factor:	>0.9
Operating Temp:	-30C (-22F) to a maximum of +45C (+113F)
Enclosure Rating:	Enclosed Rated Lamp
Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Technology:	LED
Material:	Aluminum / Plastic

DIMENSIONS

MOL:	8.43"
MOD:	3.62"
Weight:	1.65

		GS
	\mathbf{I}	

Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PRDYRJJ3
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Area and Roadway Luminaires (Type B)
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
IP Rating:	IP64
RoHS Compliant:	Yes
FCC Compliant:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923289309 Inner UPC:	20045923289303	Case UPC:	10045923289306
Each Quantity:	1 Inner Quantity:	6	Case Quantity:	12
1 Ea dhe Birthandsi Bhvad.	10.15 x 4.0 ៦ ixt 4់ស្រូ វ៉ាon C enters Dimensions:	1M2a.t6d7m2a18T4621-Fcr2e4e.74"	Case Dimensportingh	t 20127264 x 13.31 x 11.54"
В ;	, Flo		Satco Pro	oducts, Inc.
PH 631-243-2022	Texas, Washington,	(800-437-2826)	All Rights	s Reserved
FX 631-243-2027	California, Puerto Rico	www.satco.com	May 22, 2022	