



S29394

54W/LED/HID/5000K/100-277V/EX39
54 watt - LED HID Replacement; 5000K; Mogul extended base;
100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Shatter resistant materials, acceptable for use in food prep areas



S29394

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-929](#)

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
S29394	Hi-Pro	045923293948	100 - 277	54	50/60Hz	300W	85W

HID Equivalent	Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
250W	Mogul Extended	EX39	54W/LED/HID/5000K/100-277V/EX39		Non-Dimmable	White	10-3/4"	3.69"
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Burning Position	Operating Temperature	
7200	50000	5000	Natural Light	80+	300	Up or Down Operation Only	-20C (-4F) to a maximum of +65C (+149F)	
Pack	Package Type	CEC Status	DLC ID:		RoHS Compliant	UL Classification	Warranty	
12	Box	Lawful for sale in California	PLGVDTP7L3LM DLC Search		Yes	cULus - Wet Location Rated	5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

