

S29978

15T8/LED/48-850/DR

15W T8 LED; Medium bi-pin base; 5000K; 50000 Average rated hours; 2200 Lumens; Type A; Ballast dependent



Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

S29978

Ballast required.

View:

Ballast Compatibility Chart

Item Number UPC			Watts	Fluorescent ts Equivalent		Lamp Shape	Base	ANSI Base La		mp Code
S29978	045923299780		15	25W-32W		Т8	Medium Bi- Pin	G13	15T8/LE	ED/48-850/DR
Dimmable/Non-Dimmable Finish		Finish	MOL In Inches		MOD In Inches	Initial Lumer	Average R		Kelvin Temp	Color
Non-Dimmable Gloss White		48"		1.00"	2200	50000	0	5000	Natural Light	
CRI Beam Operating Temperature Pack					Package Type	CEC St	CEC Status DLC		:	RoHS Compliant

210 -20C (-4F) to a maximum of +45C (+113F) 10 Box Lawful for sale in PLU60AYH8Y7K California DLC Search

 UL or ETL Listed
 UL Classification
 Warranty

 Yes
 cULus - Damp Location Rated
 5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051