

S29991

10T8/LED/36-835/DR 10W T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1400 Lumens; Type A; Ballast dependent

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
 Compatible with emergency ballasts*
- 25watt Fluorescent equivalency
- 5 year Limited warranty

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

Ballast required

View:

Ballast Compatibility Chart

Yes

S29991

5 Year Limited

| Item Number | | UPC | | Watts | Fluorescent Equivalent | | Lamp Shape | Base | | ANSI Base | L | Lamp Code | |
|-----------------------|-------------------|---|--------|-------------|---------------------------|-------------------|----------------------------------|---------------|------|----------------------------|----------------|-------------------|--|
| S29991 045923299 | | | 9919 | 10 | | 25W | Т8 | T8 Mediu P | | G13 | 10T8/L | ED/36-835/DR | |
| Dimmable/Non-Dimmable | | | Finish | MOL Incl | | | Initial Lumens Av | | _ | | Kelvin Temp | Color | |
| Non-Dimmable W | | | White | 36" | | 1.00" | 1400 | | 5000 | 50000 | | Warm White | |
| CRI | Beam Spread De | ()nerating Lemna | | | Pack | Package Type | CEC Sta | CEC Status | | DLC ID: | | RoHS Compliant | |
| 82 | 220 | -20C (-4F) to a maximum of +45C (+113F) | | | 10 | Вох | Lawful for sale in California | | | PLQ3GM28DRVE DLC Search | | Yes | |
| UL or ETL Listed | | | | | | UL Classification | | | | Warranty | | | |

cULus - Damp Location Rated



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051