

S39390

18W/LED/HID/5000K/100-277V/E26 18 watt LED HID Replacement; 5000K; Medium base; 100-277

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size									
Length	Width	Depth							
8.5 inch	6 inch	6 inch							

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39390

S393	90	Hi-Pro	04	459233	303906	100 - 2	77	18	50/6	0Hz	120W		32W	
HID Eqi	uivalent	: Base	,	NSI ase		Lamp	Code			Dimmable Dimma		Finish	MOL I Inche	
70	W	Mediu	m E	26	18W/LE	ED/HID/500	0K/100-	·277V/E26		Non-Dimr	mable	White	5.5	2-3/8"
Initia Lume		Average Ηοι			lvin emp	Color	CRI	Beam Sp Deg		Burnin	g Position			Temperature
2520 5000		00	50	000	Natural Light	80	300			or Down ation Only	-200	. ,	a maximum of (+149F)	
Pack Package Type CEC Status Material RoHS Compliant UL or ETL Listed UL Classification Warranty									Warranty					
48	В	ох	Non-C	omplia	ant A	Aluminum	,	Yes		Yes	cULus - Damp Location Rated		5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051