

S39397

120W/LED/HID/5000K/100-277V/EX39 120 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP64 rated

- For outdoor & indoor use
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor > 0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60HzWorking Voltage AC90-305V
- Built in Surge Protection: 6KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
9.25 inch	9.25 inch	17.32 inch				

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39397

Item	Product	UPC	Input		Operating	Incandescent	Fluorescent	
Number	Line		Voltage Watts		Frequency	Equivalent	Equivalent	
S39397	Hi-Pro	045923303975	100 - 277	120	50/60Hz	750W	200W	

	livalent	Base	Base		Lamp Code			nmable/Non- Dimmable	Finish	Inches	MOD In Inches	
60	00W	Mogul Extended	EX39	120W/	120W/LED/HID/5000K/100- 277V/EX39		No	n-Dimmable	White	9-3/4"	4-23/32"	
	itial mens	Average Rated Hours	Kelvin Temp	- Co	lor CR	Beam Spre Deg	ad Bı	urning Position	Оре	erating Te	mperature	
17	7160	50000	5000	Natu Lig	80	300		Up or Down Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pack	Packag Type	CEC SIMILS	DLC	D:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	on War	rantv	Thermal lanagement	
12	Вох	Lawful for sale in California	LZWRGC		Aluminum	Yes	Yes	cULus - Damp Location Rate		<u>ear</u> <u>M</u> nited	ore Details About	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051