

S39671

22W/LED/HID/2700K/100-277V/E26

22 watt LED HID Replacement; 2700K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size							
Length	Width	Depth					
8.5 inch	6 inch	6 inch					

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406

Lisarco!	-		
	Tat	LISATO	1
Comment Mile		SSATE	

S39671

Item	Product	UPC	Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	UFC	Voltage	vvalls	Frequency	Equivalent	Equivalent

S396	71	Hi-Pro	0459	923306716	100 - 277	2	2 50	0/60Hz	15	50W		40W
HID Equ	uivalent	Base	ANS Bas		Lamp Co	ode		Dimmab Dimm		Finish	MOL In Inches	MOD In Inches
100	W	Mediur	m E26	6 22W/LE	ED/HID/2700K	/100-2	77V/E26	Non-Din	nmable	White 5	5-11/16"	2-3/8"
Initial Lu	umens	Average Ho	e Rated urs	Kelvin Temp	Color	CRI	Beam Spi Deg	read Burn	ing Position	Opera	ting Tem	perature
286	60	500	000	2700	Warm White	80	300	ι	Iniversal	•	F) to a m 65C (+14	aximum of I9F)
Pack	Pack Ty	9	CECS	Status	Material		RoHS Impliant	UL or ET Listed	L UL (Classificatio	'n	Warranty
48	Bo	х	Lawful fo Calif		Aluminum		Yes	Yes	cULus -	Damp Loca Rated	ation 5	Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051