


Project Name

Prepared By



## 17T8/LED/48-830/BP/SE-DE

Notes

General	
Status	Active
Watts	17
Volts	120-277V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Finish	Gloss White
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	2100
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Т8
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	0.2

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	0.2
Operating Temperature	-20C (-4F) to a maximum of 45C ( 113F)

Physical	
MOL	48.00
MOD	1.1
Material	Glass
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.44

## Additional Information

5 Year Limited - T8 LED Bulbs -Warranty Ballast Bypass

Compliance	
Safety Listing	cULus Classified
Location Rating	Damp
California Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes





