



S39978

15T8/LED/48-850/DR
 15W T8 LED; Medium bi-pin base; 5000K; 50000 Average
 rated hours; 2200 Lumens; Type A; Ballast dependent

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- All glass tube

*May not be compatible with every ballast. Refer to the ballast compatibility chart.

Ballast required.

View:

- [Ballast Compatibility Chart](#)
- [Dimmable Ballast Compatibility Chart](#)
- [Emergency Ballast Compatibility Chart](#)



S39978

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code	
S39978	045923399787	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-850/DR	
Dimmable/Non-Dimmable	Suggested Dimmers		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
Dimmable* Ballast Dependent	Check Ballast MFG for Dimmer Compatibility		Gloss White	48"	1.00"	2200	50000	5000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	
Natural Light	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Sleeve	Lawful for sale in California	PLN4T32YY4OE	
RoHS Compliant		UL or ETL Listed		UL Classification			Warranty	
Yes		Yes		cULus - Damp Location Rated			5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

