

# S4347 PAR56 Sealed Beams

DISCONTINUED POSS SUB  
S4811

|                  |              |
|------------------|--------------|
| <b>Lamp Type</b> | Sealed Beams |
| <b>Bulb Type</b> | PAR56        |
| <b>Base Type</b> | GX16d        |
| <b>Wattage</b>   | 300          |



## Lighting Facts Per Bulb

|   |                    |
|---|--------------------|
| <b>Brightness</b>   | <b>3840 lumens</b> |
| <b>Estimated Energy Cost</b>  | <b>\$36.14</b>     |
| per year, based on 3 hrs/day, 11c/kWh.<br>Energy cost depends on utility rates and light use. |                    |
| <b>Average Life</b>   | <b>1.8 years</b>   |
| Based on 3 hrs/day  |                    |
| <b>Light Appearance</b>   |                    |
|   |                    |
| <b>Energy Used</b>  | <b>300 watts</b>   |

## Product Information

### Features

- Display lighting
- Emergency lighting
- Equipment lighting
- 130 volt

## Product Specifications

| Item Number | Technology   | UPC                   | Voltage         | Watts         | Incandescent Equivalent | Lamp Shape     | Base                |
|-------------|--------------|-----------------------|-----------------|---------------|-------------------------|----------------|---------------------|
| S4347       | Sealed Beams | *                     | 130             | 300           | n/a                     | PAR56          | Mogul End Prong     |
| ANSI Base   | Lamp Code    | Dimmable/Non-Dimmable | Finish          | MOL in inches | MOD in inches           | Initial Lumens | Average Rated Hours |
| GX16d       | 300PAR56/WFL | n/a                   | n/a             | 5             | 7                       | 3840           | 2000                |
| Kelvin Temp | Color        | CRI                   | Beam Spread Deg | Pack          | Package Type            | ENERGY STAR    | RoHS Compliant      |
| n/a         | n/a          | n/a                   | 37              | 12            | Box                     | n/a            | Yes                 |