

S8534

9WPLH/LED/850/BP/2P 9W LED PL 2-Pin; 5000K;1000 Lumens; G24d base; 50000 Average rated hours; 120 Deg. beam spread; Horizontal; Type B; Ballast Bypass



Features

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs
- Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving

120

82

S8534

Yes

5 Year Limited

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Horizontal

Operation

50/10

Item Number	UPC	Voltage	Watts		erating quency	Fluoresc	ent Equivalent	Lamp Shape	Base
S8534	045923085345	120-277	20-277 9)/60Hz	18, 26, G24d Socket; 13, 18, 26 G24q Socket		PL	G24d
Lamp Code		Dimmable/Non- Dimmable		Finish	MOL In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
9WPLH/LED/850/BP/2P		Non-Dimmable		Frost	6-5/8''	1000	50000	5000	Natural Light
CRI Beam Spread Burning Position Pack P				ackage Type		CEC Status	atus RoHS Complia		arranty

Box

Lawful for sale in

California



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051