



S8537

9WPLV/LED/835/BP/2P
 9W LED PL 2-Pin; 3500K; 950 Lumens; G24d base; 50000
 Average rated hours; 120 Deg. beam spread; Vertical; Type B;
 Ballast Bypass

Features

- In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13, 18, and 26 watt CFLs
- Ballast Bypass; Direct wire voltage range 100-277V
- Instant on to full brightness / no flickering
- Vertical operation
- Up to 70% energy saving



S8537

Installation Note: 2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S8537	045923085376	120-277	9	50/60Hz	18, 26, G24d Socket; 13, 18, 26 G24q Socket	PL	G24d

Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
9WPLV/LED/835/BP/2P	Non-Dimmable	Frost	4-11/16"	950	50000	3500	Neutral White

CRI	Beam Spread Deg	Burning Position	Pack	Package Type	CEC Status	RoHS Compliant	Warranty
82	120	Vertical Operation	50/10	Box	Lawful for sale in California	Yes	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

