



S8692

13T5/LED/46-850/BP/HE/120-277V
 13W T5 LED; Miniature bi-pin base; 5000K; 50000 Average
 rated hours; 1700 Lumens; 120-277V; Type B; Ballast Bypass;
 Single Ended Wiring

Features

- No ballast or external driver required
- All glass tube
- PETa€shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8692

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S8692	045923086922	120-277	13	50/60Hz	T5	Miniature Bi-Pin	G5
Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
13T5/LED/46-850/BP/HE/120-277V	Frosted	48"	0.88"	1700	50000	5000	Natural Light
CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PL1ES1XSI0M3 DLC Search	Yes	Yes
UL Classification						Warranty	
cULus Classified - Damp Location Rated						5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

