

## S8697

16T5/LED/36-840/BP/HO/120-277V 16W T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 1850 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

## Features

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8697

Item	Item Number UPC			Voltage	Wa	tts Operating	g Frequency	Lamp Shape	Base	ANSI Base	
S	S8697 0459230869		77	120-277	16	50/	/60Hz	T5	Miniature Bi-Pin	G5	
Lamp Code			Finish	MOL Inch		MOD In Inches	Initial Lumen	Average Ra s Hours	ted Kelvin Temp	Color	
16T5/	16T5/LED/36-840/BP/HO/120- 277V			36	'	0.88"	1850	50000	4000	Cool White	
CRI	Beam Spread De	operating	Tempera	ture Pa	ck	CEC Status	RoHS Complia	UL or ET nt Listed	L UL Class	ification	
83	240		-20C (-4F) to a maximum of +45C (+113F)			awful for sale in California	Yes	Yes		cULus Classified - Damp Location Rated	
Warranty											
<u>5 Year Limited</u>											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

