



S8716

100W/LED/HID/5000K/277-347VEX39
 100 watt - LED HID Replacement; 5000K; Mogul extended base; 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9



S8716

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-935](#)

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent		
S8716	Hi-Pro	045923087165	277-347	100	500W	150W	400W		
Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	
Mogul Extended	EX39	100W/LED/HID/5000K/277-347VEX39		Non-Dimmable	White	9-5/8"	5.87"	13300	
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack	Package Type	

50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	4	Box
CEC Status	DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification	Warranty	
Lawful for sale in California	PLMWC6ZM5OZY; PLPGLEG6HHQ5 DLC Search		Yes	Yes	cULus - Damp Location Rated	5 Year Limited	



National Toll-Free:
 800.43.SATCO
 (800.437.2826)
www.satco.com

Distribution Centers:
 New York, Florida, Texas,
 Washington, California,
 Puerto Rico

Corporate Offices:
 110 Heartland Blvd.,
 Brentwood, NY 11717
 800.437.2826 631.243.2022
 Fax 631.243.2027

