



S9902

9T8/LED/24-840/BP 120-277V
9 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 1150 Lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- Double ended wiring
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9902

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

This item has been discontinued.

Possible replacement:

- [S29902](#)

Item Number	UPC	Input Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S9902	045923099021	120 - 277	9	50/60Hz	T8	Medium Bi-Pin	G13
Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
9T8/LED/24-840/BP 120-277V	Non-Dimmable	White	24"	1.00"	1150	50000	4000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant
Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Lawful for sale in California	PS5CFUSZ DLC Search	Yes

UL or ETL Listed	UL Classification	Warranty	Status	Suggested Substitute
Yes	cULus Classified - Damp Location Rated	5 Year Limited	Discontinued	S29902



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

