


S9927

12T8/LED/36-835/BP 12 watt T8 LED; Medium bi-pin base; 3500K; 50000 average rated hours; 1400 lumens

Features

- All glass tube
 Direct wire 120-277V line voltage*
 Double ended wiring
 NSF Approved
 No ballast or external driver required
 Built-in shock resistant circuit (not hot until both ends are installed)





59927	
-------	--

Item Numl	per UPC	Voltage	Watts	Opera Freque		Fluorescent Equivalent	Lamp Shape	Base
S9927	045923099274	120-277	12	50/60Hz		25W	Т8	Medium Bi- Pin
ANSI	Lamp Code	Dimmable	/Non-	Finish	MOL In	MOD In	In 10 at 1 ann an a	Average Rated
Base	Lamp Code	Dimma	ble	FILISH	Inches	Inches	Initial Lumens	Hours
Base G13	12T8/LED/36-835/BP	Dimma Non-Dimr		White	Inches 36"	Inches 1.00"	1400	

Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	RoHS Compliant	
3500	Neutral White	82	220	10	Вох	Lawful for sale ir California	n Yes	
UL or ETL Listed				UL Class		Warranty		
Yes			cULus	s - Damp	Location Rated		5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051