

## S9928

12T8/LED/36-840/BP 12 watt T8 LED; Medium bi-pin base; 4000K; 50000 average rated hours; 1450 lumens

## Features

- All glass tube

- All glass tube
  Direct wire 120-277V line voltage\*
  Double ended wiring
  NSF Approved
  No ballast or external driver required
  Built-in shock resistant circuit (not hot until both ends are installed)



This item has been discontinued. Possible replacement:

• S29928



S9928

Item Numbe	er UPC	;	Voltage	Watts	5	Opera Frequ	_	Fluoresce Equivale		Lamp Shape	Base
S9928	04592309	9281	120-277	12		50/60	OHz	25W		T8	Medium Bi- Pin
ANSI Base	Lamp Code		Dimmable/Non- Dimmable		F	Finish MOL In Inches			Initia	al Lumens	Average Rated Hours
G13 1	2T8/LED/36-84	0/BP	Non-Dimn	nable	١	White	36"	1.00"		1450	50000
Kelvin Tem	p Color	CRI	Beam Spread	d Deg	Pack	Pac	ckage Type	e CEC	Status	; F	RoHS Compliant
4000	Cool White	82	220		10		Box	Lawful	for sale	in	Yes

Kelvin Temp Color		CRI	CRI Beam Spread Deg		Package Type	CEC Status		RoHS Compliant
4000 Cool White		82	82 220		Box	Lawful for sale in California		Yes
UL or ETL Lis	sted	UL Classification			Varranty	Status	Suggested Substitute	
Yes	cULu	cULus - Damp Location Rated			ear Limited	Discontinued		<u>S29928</u>



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051