



S9931

15T8U6/LED/22.5-835/BP
15W T8 U-Bend LED; Medium bi-pin base; 3500K; 50000
Average rated hours; 1700 Lumens; Type B; Ballast Bypass;
Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

S9931

* Install only in non-shunted lampholders

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	Lamp Code	Dimmable/Non-Dimmable
S9931	045923099311	15	50/60Hz	T8	Medium Bi-Pin	15T8U6/LED/22.5-835/BP	Non-Dimmable

Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
White	22.5"	7.00"	6"	1700	50000	3500	Neutral White

CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	P5DE5AYV DLC Search	Yes

UL or ETL Listed	UL Classification	Warranty
Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

