

S9937

11.5T8/LED/48-850/DR 11.5 watt T8 LED; Medium bi-pin base; 5000K; 50000 average rated hours; 1800 lumens

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View: Ballast Compatibility Chart Emergency Ballast Compatibility Chart

This item has been discontinued. Possible replacement:

• <u>S29937</u>

Fluorescent Lamp ANSI Item Number UPC Watts Base Lamp Code Equivalent Shape Base Medium Bi-Τ8 S9937 045923099373 11.5 25W-32W G13 11.5T8/LED/48-850/DR Pin MOL In MOD In Average Rated Kelvin Dimmable/Non-Dimmable Initial Lumens Finish Color Inches Inches Hours Temp 48" 1.00" 50000 Non-Dimmable White 1800 5000 Natural Light Beam Spread UL or ETL CRI Pack Package Type **CEC** Status DLC ID: **RoHS** Compliant Deg Listed



82	220	10	Box	Lawful for sale in California	PA4P1QV4 DLC Search	Yes	Yes
UL Classification				Warranty	Status	Suggested Substitute	
cULus - Damp Location Rated				5 Year Limited	Discontinued	<u>S29937</u>	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051