

SOFTLINE™ MR16

FROSTED LAMPS with FROSTED FRONT GLASS

USHIO Softline™ series of MR16 lamps feature a frosted front glass cover. The frosted front glass cover reduces glare and evenly distributes white Halogen light without dark spots or striations. The UV protected Halogen capsule is computer aligned inside a Titanium Oxide coated reflector. The proper alignment of the filament and the reflector ensures a precise beam pattern. The hard Titanium Oxide surface provides consistent color throughout the life of the lamp. The USHIO Softline lamps are available in 20W, 35W, 50W and 75W.

FEATURES & BENEFITS:

- Reduces Glare
- Creates Soft Beam of White Halogen Light
- Integrated Frosted Cover Glass
- Consistent Color
- 4000 Hours Average Life
- Dimmable
- UV Protected
- Axial Filament

APPLICATIONS:

- Accent Lighting
- Museums and Galleries
- Decorative Lighting
- Restaurants
- Track Lighting
- Display Lighting



GU5.3

Case Quantity: 50

Watts (W)	Ordering Code	Lamp Description	Voltage (V)	Dimension MOL (in)	Color Temp (K)	Beam Angle	Luminous Intensity (cd)	Average Rated Life (h)
SOFTLINE™ MR16 Frosted Front Glass Cover, 2-Pin Base								
20	1003284	JR12V-20W/FL30/FG/SFT	12	1.78	2950	30°	400	4000
35	1003285	JR12V-35W/FL30/FG/SFT	12	1.78	2950	30°	700	4000
50	1003286	JR12V-50W/FL30/FG/SFT	12	1.78	2950	30°	1200	4000
75	1003287	JR12V-75W/FL30/FG/SFT	12	1.78	2950	30°	1600	3500

All dimensions shown in inches unless otherwise noted.



Softline™ lamps are manufactured under ISO 9001 guidelines ensuring quality and security for the purchaser.

ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)
1.77	3.3	37.16	1.77	3.3	65.03	1.77	3.3	111.48	1.77	3.3	148.64
3.51	6.5	9.29	3.51	6.5	16.26	3.51	6.5	27.87	3.51	6.5	37.16
5.28	9.8	4.09	5.28	9.8	7.25	5.28	9.8	12.36	5.28	9.8	16.54
7.02	13.1	2.32	7.02	13.1	4.08	7.02	13.1	6.97	7.02	13.1	9.29
30° JR12V-20W/FL30/FG/SFT 20W			30° JR12V-35W/FL30/FG/SFT 35W			30° JR12V-50W/FL30/FG/SFT 50W			30° JR12V-75W/FL30/FG/SFT 75W		



Form No. S-MR16SOFTLINE/0615

Specifications may be subject to change without prior notice. Refer to www.ushio.com for the most current product specifications.