USHIO

# **IR MR16 REFLECTOR LAMPS**

#### EUROSTAR™ IR 12 VOLT SERIES



### INFRARED (IR) MR16 LAMPS FOR GENERAL LIGHTING

Consumers today demand energy-saving, long life lighting options that will not sacrifice the quality of their lighted environment. USHIO's new Eurostar<sup>™</sup> IR Infrared Halogen MR16 lamps fulfill both of these demands. They reduce energy consumption by 30% compared to standard halogen MR16 lamps, they last an average of 6,000 hours and they maintain the crisp, white halogen light and superior beam control that makes any application look its best.

Thanks to an advanced infrared-reflective film coating process applied to the halogen capsule which allows visible light to pass through the glass envelope while reflecting the infrared energy back to the filament. These lamps are able to produce a high light output while maintaining an optimum operating temperature and reduce the energy used by the lamp.

In addition to the advanced capsule design, the Eurostar<sup>™</sup> IR lamps incorporate the same premium characteristics that other lamps in the Eurostar<sup>™</sup> MR16 family feature. This includes the multi-layer titanium oxide coated reflector that allows the lamp to produce consistent color throughout life, as well as the precision aligned axial filament for optimal beam control.

The Eurostar<sup>™</sup> IR lamp series has the longest rated life of any IR MR16 lamp on the market. At 6,000 hours average rated life the Eurostar<sup>™</sup> IR lamps offer 20% greater life than other IR MR16 lamps and 50% more life than some standard MR16 lamps.

Available in 37W and 50W versions in Spot 9°, Narrow Flood 25°, Flood 35° and Wide Flood 60° beam spreads.

### **FEATURES & BENEFITS**

- Special IR technology provides up to 30% energy savings
- 37W Eurostar<sup>™</sup> IR MR16 replaces standard 50W halogen MR16
- 50W Eurostar™ IR MR16 replaces standard 75W halogen MR16
- Long Life 6,000 hour average life
- Halogen capsule cuts harmful UV Reduces the amount of material wear from harmful UV radiation
- Advanced titanium oxide coating Consistent color throughout lamp life
- Axial filament Provides optimal light output and consistent beam spreads
- Crisp white Halogen light

#### **APPLICATIONS**


- Museums and Galleries
- Retail Shops
- Offices & Commercial Areas
- Hotels & Restaurants
- Track Lighting
- Accent Lighting


# USHIO **12V EUROSTAR<sup>™</sup> IR**

GU5.3 Base C-6 Filament **Universal Burn Position** Case Quantity: 20

2.07

9° JR12V-50W/SP/FG/IR 50W





ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)
0.52	3.3	1208	<u>1.45</u>	3.3	409	<u>2.07</u>	3.3	204	<u>3.79</u>	3.3	102
1.03	6.6	302	<u>2.91</u>	6.6	102	<u>4.14</u>	6.6	51	7.58	6.6	26
1.55	9.8	134	4.36	9.8	45	<u>6.21</u>	9.8	23	11.37	9.8	11
<u>2.07</u>	13.1	75	5.82	13.1	26	8.28	13.1	13	<b>15</b> .15	13.1	6
<b>9°</b> JR1:	2V-37W/SP/FG/	ir 37W	25° JR12	V-37W/NFL/FG	ir <b>37W</b>	35° JR12	2V-37W/FL/FG	/IR <b>37W</b>	60° JR12	2V-37W/WFL/F0	G/IR <b>37W</b>
a (ft)	LJ <i>(</i> #+)	E(fo)	c/f#)	LJ <i>(</i> #+)	E(fo)	c/ft)	LJ <i>(</i> #+)	E/fa)	c/f#)	LJ(#+)	E(fo)
ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)	ø(ft)	H(ft)	E(fc)
0.52	3.3	1440	1.45	3.3	529	<u>2.07</u>	3.3	260	3.79	3.3	130
1.03	6.6	360	2.91	6.6	132	<u>4.14</u>	6.6	65	7.58	6.6	33
<u>1.55</u>	9.8	160	4.36	9.8	59	<u>6.21</u>	9.8	29	<u>11.3</u> 7	9.8	14

33

8.28

35° JR12V-50W/FL/FG/IR 50W

Distributed by:

16

Watts (W)	Ushio Ordering Code	Ushio Lamp Description	MOL (in)	Color Temp (K)	Beam Angle	Beam Spread	Luminous Intensity (cd)	Avg Life (h)
37	1003706	JR12V-37W/SP/FG/IR	1.99	3000	9º	Spot	13000	6,000
37	1003705	JR12V-37W/NFL/FG/IR	1.99	3000	25°	Narrow Flood	4400	6,000
37	1003704	JR12V-37W/FL/FG/IR	1.99	3000	35°	Flood	2200	6,000
37	1003707	JR12V-37W/WFL/FG/IR	1.99	3000	60°	Wide Flood	1100	6,000
50	1003710	JR12V-50W/SP/FG/IR	1.99	3000	9º	Spot	15500	6,000
50	1003709	JR12V-50W/NFL/FG/IR	1.99	3000	25°	Narrow Flood	5700	6,000
50	1003708	JR12V-50W/FL/FG/IR	1.99	3000	35°	Flood	2800	6,000
50	1003711	JR12V-50W/WFL/FG/IR	1.99	3000	60°	Wide Flood	1400	6,000



Scan with a smartphone to view this product online.

Form No. S-IRMR16 EUR012V/0811: Specifications may be subject to change without prior notice. Refer to www.ushio.com for the most current product specifications.

90

5.82

25° JR12V-50W/NFL/FG/IR 50W

## **CHARACTERISTICS & SPECIFICATIONS**

USHIO America, Inc. • www.ushio.com

<b>U</b> ()	• •(••)	=()				
3.79	3.3	130				
7.58	6.6	33				
<u>11.3</u> 7	9.8	14				
<b>15</b> .15	13.1	8				
60° JR12V-50W/WFL/FG/IR 50W						

© 2011 USHIO America, Inc. All rights reserved.

